



Features: Double Layers

Item No. / 產品型號	TD-015	TD-025
Specifications / 規格		
Total Length / 總長度 (L) [mm]	8.5 x P + 32 mm	10 x P + 32 mm
Ref. Length / 內長度 (L1) [mm]	8.5 x P + 16 mm	10 x P + 18 mm
Gap (A) [mm]	7 mm	8 mm
Pitch / 節距 (B) [mm]	8.5 mm	10 mm
Screws / 螺絲 (C)	M3	M4
固定孔孔徑 (D) [mm]	4.5 mm	4.5 mm
Width / 寬度 (W) [mm]	40 mm	50 mm
Ref. Width / 參考寬度 (W0) [mm]	28 mm	32 mm
Ref. Width / 參考寬度 (W1) [mm]	20 mm	20 mm
Height / 高度 (H) [mm]	40 mm	50 mm
Electrical Specifications / 電氣規格		
Rated Voltage / 額定電壓 [V]	600 V	600 V
Rated Current / 額定電流 [A]	15 A	25 A
Temperature / 耐熱溫度 [°C]	110 °C	110 °C
Poles / 極數 (P)	Any / 任意 P 數	Any / 任意 P 數
Materials / 材料		
Base Materials / 基座材料	PC / Nylon 66 工程塑膠	PC / Nylon 66 工程塑膠
Color / 顏色	Black / 黑	Black / 黑
Flame Retarded Grade / 防火等級	UL 94V-2 / UL 94V-0	UL 94V-2 / UL 94V-0
Conductor / 銅片材料	Brass / 黃銅	Brass / 黃銅
Accessories & Parts / 零配件		
Paper Strip / 紙條 [mm]	7 mm	7 mm
End Plate / 邊片	Two Sides / 左右邊片	Two Sides / 左右邊片
Transparent Cover / 透明片 [mm]	0.5 x 22.3 / 13.4 mm	0.5 x 22.3 / 13.4 mm
Steel Rod / 鐵條 [mm]	3 mm	3 mm
Protective Cover / 防塵蓋	N/A	N/A
DIN Mount Rail / 軌道 [mm]	35 mm / 25.5 mm	35 mm / 25.5 mm
End Clamp / 煞車擋片	TA-002 / TA-002H / TE-002	TA-002 / TA-002H / TE-002